

With the new Eutech Testr 35 series, multi-parameter measurement is a breeze. Convenient, fast and simple, all you need to do is dip, measure and scan through up to five parameters with the press of a button. No complicated operating procedures; no need to change sensors for different parameter measurement.



Waterproof Multi-Parameter Testers Testr 35 Series

• pH • Conductivity • TDS • Salinity • Temperature

SOLUTIONS FOR WATER ANALYSIS

EUTECH
INSTRUMENTS
Technology Made Easy ...

One Tester, Up to Five Parameters: Water Analysis that Fits Your Pocket!

Simple, Stress-Free Operation

- One-Button Parameter Toggle- Scan through Multiple Parameter Readings by Simply Pressing a Button
- Self-Diagnostic with Instutive Prompts

Convenient, Accurate Measurements

- More Calibration Options-Single/Point or Auto/ Manual Calibration
- Measure Conductivity/TDS More Accuracy at Varying Temperature with Adjustable Temperature Coefficient Feature

Fast-Responding

- Unique Sensor Design for Faster ATC Response and Faster Reading
- Auto-Ranging-Speedy and Convenient for Application with Broad Measurement Ranges



Waterproof
Multi-Parameter
Testers

Testr 35 Series



Large Custom
Dual-Display LCD



One Sensor
Measurement Up To
5 Parameters



User-Replaceable
Sensor



Ip67 Waterproof
Tester Floats
On Water



Specification

		PCSTestr 35	PCTestr 35	PTTestr 35
pH	Range	0.00 to 14.00	pH 0.0 to 14.0	pH 0.0 to 14.0 pH
	Resolution	0.01 pH	0.1 pH	0.1 pH
	Accuracy	0.01 pH	0.1pH	0.1 pH
	Cal. Points	Up to 5 (auto)	Up to 5 (auto)	Up to 5 (auto)
	Auto-Buffer	Yes	Yes	Yes
	Recognition			
Cond.	Range	0.0 to 199.9 μ S/cm 200 to 1999 μ S/cm 2.00 to 20.00 mS/cm	0 to 1999 μ S/cm 2.00 to 20.00 mS/cm	–
	Resolution	0.1 μ S/cm / 1 μ S/cm / 0.01 mS/cm	1 μ S/cm / 0.01 mS/cm	–
	Accuracy	\pm 1 % full scale	\pm 1 % full scale	–
	Cal. Points	3 auto, 3 manual	2 auto, 2 manual	–
	Temperature	0.0 to 10.0 %/°C	0.0 to 10.0 %/°C	0.0 to 10.0 %/°C
	Coefficient			
	Normalisation	25.0 °C	25.0 °C	25.0 °C
	Temperature			
	Auto-Ranging	Yes	Yes	Yes
TDS	Range	0.0 to 99.9 ppm 100 to 999 ppm 1.00 to 10.00 ppt	–	0 to 999 ppm / 1.00 to 10.00 ppt
	Resolution	0.1 ppm / 1 ppm / 0.01 ppt	–	1 ppm / 0.01 ppt
	Accuracy	\pm 1 % full scale	–	\pm 1 % full scale
	Cal. Points	Up to 3 (manual)	–	Up to 2 (manual)
	TDS Factor	0.40 to 1.00	–	0.40 to 1.00
Salinity	Range	0.0 to 99.9 ppm 100 to 999 ppm 1.00 to 10.00 ppt 0.0 to 1.00 %	–	–
	Resolution	0.1 ppm / 1 ppm 0.01 ppt / 0.01 %	–	–
	Accuracy	\pm 1 % full scale*	–	–
	Cal. Points	1 (manual, above 1.00 ppt)	–	–
Temp.	Range		0 to 50.0 °C / 32 to 122.0 °F	
	Resolution		0.1 °C / 0.1 °F	
	Accuracy		0.5 °C / 0.9 °F	
Temp. Compensation			ATC / MTC	
Sensor Type			pH / Conductivity / TDS / Salinity / Temperature	
Non-Volatile Memory			Yes	
Auto-Off			8.5 mins after last key pressed (can be disabled)	
LCD Display			Dual-display LCD (2.1 x 2.7 cm)	
Power			4 x 1.5 V "A76" micro alkaline batteries	
Dimensions ; Weight			Tester: 16.5 cm x 3.8 cm ; 90 g Boxed: 18.5 cm x 6.5 cm x 5 cm ; 200 g	

Ordering Information

Order No.	Stock Code	Item
PCSTEST35	01X441506	Waterproof PCSTestr 35
PCTEST35	01X441504	Waterproof PCTestr 35
PTTEST35	01X441505	Waterproof PTTestr 35
PCSENSOR	01X097108	Replacement pH/Conductivity/ Temperature Sensor



Complimentary Lanyard
with every tester purchased

Certified IP67 Waterproof
Tester even floats for
easy retrieval!

ATC/MTC Option
Accurate readings even in
varying condition

Accurate Readings with
High Resolution of up to
two-decimal places

Scroll-Menu with Four
Buttons Control
Navigating through
function and menu is
easy as a breeze!

Twist-and-Lock
Sensor Replacement
No tools required!

Valox® PBT Plastic
For measurements in harsh
industrial solvents and chemicals

**EUTECH
INSTRUMENTS**
Technology Made Easy ...

Part of Thermo Fisher Scientific Inc.



Distributed by:

WPT 08X233119 11/08 Rev 1

